



Ketty Ice in

| REFRIGERATORE SOTTOLAVELLO | UNDER COUNTER WATER COOLER | REFROIDISSEUR SOUS COMPTOIR | |
|--|---|--|-----------------|
| Impianto frigorifero dotato di compressore ermetico con condensazione a ventilazione forzata | Water cooler with hermetic compressor and forced ventilation condensing | Réfrigérateur avec compresseur hermétique et condensation à ventilation forcée | |
| Sistema di raffreddamento: banco ghiaccio | Cooling system: ice bank | Système de refroidissement: banc de glace | |
| Produzione d'acqua temperatura ambiente | Delivery of room temperature water | Débit d'eau à température ambiante | V |
| Produzione d'acqua fredda | Delivery of cold water | Débit d'eau froide | 25 l/h |
| Produzione d'acqua fredda frizzante | Delivery of cold sparkling water | Débit d'eau gazeuse | 25 l/h |
| Pompa booster made in italy | Pump booster made in italy | Pompe booster made in italy | 130 l/h |
| Banco ghiaccio | Ice bank | Banc de glace | 5 l |
| Gasatore | Carbonator | Carbonateur | 0,8 l |
| Assorbimento | Absorption | Absorption | 77 W |
| Potenza frigorifera | Cooling power | Puissance de réfrigération | 155 W |
| Pressione di esercizio | Operating pressure | Pression de fonctionnement | 3 bar |
| Alimentazione | Power supply | Alimentation | 230V - 50Hz |
| Compressore | Compressor | Compresseur | 1/12 HP |
| Gas R134a | Gas R134a | Gaz R134a | 78 g. |
| Rumorosità | Noise | Bruit | <67 db. |
| Dimensioni (mm) | Dimensions (mm) | Dimensions (mm) | 180 x 310 x 440 |
| Peso | Weight | Poids | 15,5 kg |
| Pannelli | Panels | Panneaux | Painted steel |
| Voltaggi speciali | Special voltages | Voltages spéciaux | Upon request |
| Allestimenti personalizzati | Personalized equipment | Équipements personnalisés | Upon request |